

# firemaster FZ

The only AS1530.8.2-2018 Tested BAL-FZ shutter



Revision 4.0 February 2020

delivering engineered solutions

# firemaster FZ

The only AS1530.8.2-2018 Tested BAL-FZ shutter

**“ANY window/door can achieve BAL-FZ compliance”**

## how do they work?

The shutter is concealed in a compact head box until it is deployed. This is installed to the exterior of an opening.

The shutter is deployed manually via the push of a button; multiple shutters can be connected to one button. It can also be deployed manually with a hand crank. The shutter can be lowered to any level for additional use as a block-out blind.

## available colours

We have 3 base colours (seen below) however can powdercoat to any desired DULUX Duralloy colour.

white satin 1139S	black matt 19319	anotec silver grey 51272
----------------------	---------------------	--------------------------------



## shutter sizes

System	Max Height	Max Width	Headbox Height	Headbox Depth
FireMaster FZ	2600mm	2400mm	200mm	150mm

## benefits

- AS3959-2018 Compliant
- Tested to AS1530.8.2-2018
- Seamless design integration
- Bushfire protection up to BAL-FZ
- Does not require any specific glass to achieve BAL rating
- Concealed in a small compact headbox above your window
- Suitable for all windows and door types
- Manual deployment via crank shaft or button
- Minimum maintenance required
- Simple retrofit solutions
- Can be used as a block-out blind

